

Premier LB02019 - D

Linear Low Density Polyethylene

Premier Polymers, LLC.

Message:

Premier LB02019 is a butene linear low density polyethylene suitable for blown/cast thin gauge applications requiring toughness and strength. Meets all requirements of the U.S. Food and Drug Administration as specified in 21 CFR 177.1520, covering safe use of polyolefin articles intended for direct food contact.

General Information			
Additive	High Antiblock		
	Medium Slip		
Features	Food Contact Acceptable		
	Good Strength		
	Good Toughness		
	High Antiblocking		
	Low Density		
	Medium Slip		
Agency Ratings	FDA 21 CFR 177.1520		
Processing Method	Blown Film		
	Cast Film		
Physical	Nominal Value	Unit	Test Method
Density	0.919	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.0	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D882
MD : Break	27.6	MPa	
TD : Break	17.2	MPa	
Tensile Elongation			ASTM D882
MD : Break	600	%	
TD : Break	800	%	
Dart Drop Impact	65	g	ASTM D1709
Elmendorf Tear Strength			ASTM D1922
MD	100	g	
TD	550	g	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT