

SABIC® LDPE 2402CX0

Low Density Polyethylene
Saudi Basic Industries Corporation (SABIC)

Message:

SABIC® LDPE 2402CX0 is a grade typically used in foam applications.
Application
SABIC® LDPE 2402CX0 can be typically used for all types of foam, produced with chemical blowing agents or physical gases, X-linked and non X-linked.
This product is not intended for and must not be used in any pharmaceutical/medical applications.

General Information			
Features	Low density		
Uses	Foam		
Processing Method	Foam extrusion molding		
Physical	Nominal Value	Unit	Test Method
Density	0.924	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.0	g/10 min	ISO 1133

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT