MonoSol® M7030

Polyvinyl Alcohol

MonoSol, LLC

Message:

MonoSol M7030 is a PVOH based thermoplastic film, soluble in cold water and manufactured using MonoSol's proprietary solution cast technology. MonoSol M7030 is a typical grade of PVOH cold water-soluble packaging film and is the film choice when there are no special requirements or contraindications. This tough film has good solubility, machinability, toughness, cold crack resistance and can be converted on all conventional packaging machines. Typical applications include Agrochemicals, Detergents, Disinfectants, Pigments and Additive Unit Dose Packaging. Standard thicknesses are 38 micron (1.5 mil) and 76 micron (3.0 mil).

| General Information | | | |
|--|---------------------------|-------|-----------------------|
| Features | Biodegradable | | |
| | Good Crack Resistance | | |
| | Good Toughness | | |
| | Low Temperature Resistant | | |
| | Machinable | | |
| | Water Soluble | | |
| | | | |
| Uses | Film | | |
| | Industrial Applications | | |
| | Packaging | | |
| | | | |
| Forms | Film | | |
| Physical | Nominal Value | Unit | |
| Moisture Content (23°C) ¹ | 6.3 | wt% | |
| Solubility ² | | | |
| Disintegration : 10°C, 38.1 μm | 16.0 | sec | |
| Disintegration : 24°C, 38.1 μm | 9.0 | sec | |
| Dissolution : 10°C, 38.1 μm | 32.0 | sec | |
| Dissolution : 24°C, 38.1 μm | 24.0 | sec | |
| Yield (38.1 μm) | 19.9 | m²/kg | ASTM D4321 |
| Films | Nominal Value | Unit | Test Method |
| Film Thickness - Recommended / Available | 38 μm and 76 μm | | |
| Secant Modulus - 100%, MD | 15.9 | MPa | ASTM D882, ISO 527-3 |
| Tensile Strength - MD | | | |
| Break | 41.4 | MPa | ASTM D882 |
| | 41.4 | MPa | ISO 527-3 |
| Tensile Elongation - MD (Break) | 410 | % | ASTM D882, ISO 527-3 |
| Dart Drop Impact | 780 | g | ASTM D1709, DIN 53433 |
| Elmendorf Tear Strength - MD | | | |
| | 1200 | g | ASTM D1922 |

| | 0.12 | N | ISO 6383-2 |
|------|-------------------------|-----|------------|
| NOTE | | | |
| 1. | 50%RH | | |
| 2. | Distilled Water (MSTM 2 | 05) | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

