SQUARE® SEP8660-70

Silicone

Shenzhen SQUARE Silicone Co., Ltd.

Message:

Silicone sealing strip for automobile engine and door Product description Basic modified silicone EPDM, with high temperature and weather resistance, and good mechanical property of EPDM. Key Features High temperature resistance, good weather resistance, good mechanical property. Application Silicone sealing strip for automobile engine and door

| General Information | | | |
|--------------------------------|---------------------------------|------|-------------|
| Features | Good weather resistance | | |
| | Heat resistance, high | | |
| | | | |
| Uses | Seals | | |
| | Application in Automobile Field | | |
| | | | |
| Hardness | Nominal Value | | Test Method |
| Durometer Hardness (Shore A) | 70 | | ASTM D2240 |
| Elastomers | Nominal Value | Unit | Test Method |
| Tensile Strength | 8.50 | MPa | ASTM D412 |
| Tensile Elongation (Break) | 380 | % | ASTM D412 |
| Tear Strength ¹ | 15.0 | kN/m | ASTM D624 |
| Compression Set (175°C, 22 hr) | 26 | % | DIN 53517 |
| Thermoset | Nominal Value | Unit | |
| Shelf Life | 100 | wk | |
| NOTE | | | |
| 1. | B mould | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

