

Ferro PE NPE00IA02NA

Polyethylene

Ferro Corporation

Message:

Ferro PE NPE00IA02NA is a Polyethylene material. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Primary attribute of Ferro PE NPE00IA02NA: Impact Resistant.

General Information			
Features	High Impact Resistance		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.878	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	6.5	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield, 23°C)	11.0	MPa	ASTM D638
Tensile Elongation (Break, 23°C)	360	%	ASTM D638
Flexural Modulus			ASTM D790
1% Secant : 23°C	110	MPa	
Tangent : 23°C	161	MPa	
Flexural Strength (Yield, 23°C)	31.7	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	No Break		ASTM D256
Unnotched Izod Impact (23°C)	No Break		ASTM D256
Gardner Impact	< 36.2	J	ASTM D5420
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	135	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT