

Vapolen 220 TPP

Polypropylene

Vatan Plastik San. Tic. AS

Message:

Vapolen 220 TPP is a Polypropylene material filled with 20% mineral. It is available in Africa & Middle East, Asia Pacific, or Europe.

Typical applications include:

- Appliances
- Electrical/Electronic Applications
- Automotive
- Furniture

General Information			
Filler / Reinforcement	Mineral,20% Filler by Weight		
Uses	Appliances		
	Automotive Applications		
	Computer Components		
	Electrical/Electronic Applications		
	Furniture		
	White Goods & Small Appliances		
Appearance	Colors Available		
Forms	Granules		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.00 to 1.10	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	3.0 to 5.0	g/10 min	ASTM D1238
Ash Content (600°C)	19 to 21	%	ISO 3451-1
Izod Impact	3.00	kJ	ISO 180
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D)	74		ISO 868
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	159	°C	ISO 306

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT