

# ASACLEAN™ PX

Proprietary

ASACLEAN - Sun Plastech Inc.

## Message:

PURGE COMPOUND FOR SCREW AND BARREL

Special glass-filled grade

Dedicated to clean high engineering resins

Temperature range : 270°C - 420°C

ASACLEAN ® PX is 50% glass-filled and is especially designed to purge high engineering resins at very high temperatures. The fields of appliance are Injection Moulding

Extrusion

It is characterized by the famous ASACLEAN ® purging power and efficiency. Smokes and smells are extremely reduced. ASACLEAN ® PX is not corrosive and is applicable for

Colour Changes

Material Changes

"Sealing"

Hot Runner Cleaning

Contact:

VELOX GmbH

Tel: +49 - (0)40 - 369 688 - 0

eMail: [info@velox.com](mailto:info@velox.com)

Website: <http://www.velox.com>

General Information	
Filler / Reinforcement	Glass Fiber,50% Filler by Weight
Features	High Heat Resistance
	Low Smoke Emission
	Low to No Odor
	Non-Corrosive
Uses	Purging Compound
Forms	Pellets
Processing Method	Extrusion
	Injection Molding

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: [sales@su-jiao.com](mailto:sales@su-jiao.com)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT