

Fainplast PVC PG 65/4

Polyvinyl Chloride + NBR

Fainplast Compounds S.r.l

Message:

Fainplast PVC PG 65/4 is a Polyvinyl Chloride + NBR (PVC+NBR) product. It can be processed by extrusion or profile extrusion and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America.

General Information			
Uses	Profiles		
Processing Method	Extrusion		
	Profile Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.30	g/cm ³	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	65		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	> 12.0	MPa	ISO 527-2
Tensile Strain (Break)	> 300	%	ISO 527-2

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

