

Epic Urethane S7445

Polyurethane

Epic Resins

Message:

Two Component Polyurethane

Epic S7445 is formulated with a low viscosity for increased flow when used in the manufacture of HEPA/Air filters. This polyurethane can be used on wood or metal substrates and provides a fast cure with a low exotherm.

Application: HEPA / Air Filter Adhesive

General Information			
Features	Fast Cure		
	Low Exotherm		
	Low Viscosity		
Uses	Adhesives		
	Filters		
Hardness	Nominal Value		Test Method
Durometer Hardness (Shore A)	83 to 88		ASTM D2240
Thermoset	Nominal Value	Unit	Test Method
Thermoset Mix Viscosity ¹ (25°C)	700 to 1000	cP	ASTM D2393
NOTE			
1.	20 RPM		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

