

# XYRON™ S202A

Polyphenylene Ether

Asahi Kasei Chemicals Corporation

Message:

XYRON™ S202A is a Polyphenylene Ether (PPE) product. It can be processed by injection molding and is available in Africa & Middle East, Asia Pacific, Europe, or North America. Primary characteristic: low viscosity.

General Information			
Features	Low Viscosity		
Forms	Powder		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	
Density	1.06	g/cm <sup>3</sup>	
Apparent Density	0.40 to 0.50	g/cm <sup>3</sup>	
Viscosity Number (Reduced Viscosity) <sup>1</sup> (30°C)	41.0	ml/g	
Mean Particle Size	200.0 to 400.0	μm	
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	214	°C	DSC
NOTE			

1. 0.5 g/dl-PPE in CHCl<sub>2</sub>

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

