

Fainplast PVC RKS 441/W

Rigid Polyvinyl Chloride

Fainplast Compounds S.r.l

Message:

Fainplast PVC RKS 441/W is a Rigid Polyvinyl Chloride product. It can be processed by extrusion and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Electrical/Electronic Applications.

| General Information | | | |
|------------------------------|------------------------------------|-------------------|-------------|
| Features | Low (to None) Lead Content | | |
| Uses | Conduit | | |
| | Electrical/Electronic Applications | | |
| | Profiles | | |
| UL File Number | E328771 | | |
| Processing Method | Extrusion | | |
| Physical | Nominal Value | Unit | Test Method |
| Density | 1.59 to 1.63 | g/cm ³ | ISO 1183 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Stress | | | ISO 527-2 |
| Yield | > 38.0 | MPa | |
| Break | > 36.0 | MPa | |
| Tensile Strain (Break) | > 80 | % | ISO 527-2 |
| Impact | Nominal Value | Unit | Test Method |
| Unnotched Izod Impact (23°C) | 50 to 70 | J/m | ISO 180 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT