

NEXUS PE LLDPE-H118

Linear Low Density Polyethylene

Nexus Resin Group, LLC.

Message:

Linear Low Density Polyethylene for blown film applications
Nexus LLDPE-H118 is designed for blown film applications such as liners, heavy duty sacks and stretch wrap. Available in various slip and antiblock packages.

General Information			
Uses	Film		
	Heavy-duty Bags		
	Liners		
	Stretch Wrap		
Processing Method		Blown Film	
Physical	Nominal Value	Unit	Test Method
Density	0.918	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.0	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D882
MD : Yield	37.9	MPa	
TD : Yield	27.6	MPa	
Tensile Elongation			ASTM D882
MD : Break	650	%	
TD : Break	900	%	
Dart Drop Impact	220	g	ASTM D1709

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT