Propilven B-328

Polypropylene Random Copolymer

Propilven, S.A.

Message:

Propilven B-328 grade is a random copolymer designed for blow molding transparent bottles. It is also used in sheet extrusion and thermoforming of glasses and trays. Special Features: High clarity and brightness Good impact strength Low level of residual odor

General Information			
Features	Good Impact Resistance		
	High Clarity		
	Low to No Odor		
	Random Copolymer		
Uses	Bottles		
	Cups		
	Sheet		
Forms	Pellets		
Processing Method	Blow Molding		
	Sheet Extrusion		
	Thermoforming		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR)	1.4	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	27.0	MPa	ASTM D638
Flexural Modulus	1000	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	110	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	80.0	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

