

Smoothblend® PC-1302

Polycarbonate

Colour Image Plastic Compound Sdn. Bhd. (CIPC)

Message:

Smoothblend® PC-1302 is a wear resistance polycarbonate compound offering superb lubricity by incorporating PTFE and carbon fiber. It is developed for applications demanding stringent wear resistant and low friction performance.

General Information			
Filler / Reinforcement	Carbon Fiber,30% Filler by Weight		
Additive	PTFE Lubricant (15%)		
Features	Good Chemical Resistance		
	Good Thermal Stability		
	Good Wear Resistance		
	Low Friction		
	Lubricated		
Uses	Automotive Applications		
	Bushings		
	Engineering Parts		
	Gears		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.55	g/cm ³	ASTM D792
Molding Shrinkage - Flow (3.20 mm)	0.10 to 0.30	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	115	MPa	ASTM D638
Tensile Elongation (Break)	2.0	%	ASTM D638
Flexural Modulus	8610	MPa	ASTM D790
Flexural Strength	180	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	190	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed, 4.00 mm)	145	°C	ASTM D648
Flammability	Nominal Value		Test Method
Flame Rating (1.60 mm)	HB		UL 94
Injection	Nominal Value	Unit	
Drying Temperature	120	°C	
Drying Time	4.0 to 6.0	hr	

Rear Temperature	275 to 280	°C
Middle Temperature	280 to 285	°C
Front Temperature	285 to 290	°C
Nozzle Temperature	290 to 295	°C
Processing (Melt) Temp	275 to 300	°C
Mold Temperature	85.0 to 110	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

