ISOTHANE® 2095A-MH

Thermoplastic Polyurethane Elastomer (Polycaprolactone)

Great Eastern Resins Industrial Co., Ltd. (GRECO)

Message:

ISOTHANE 2095A-MH product is a high performance polycaprolactone based thermoplastic polyurethanes. It exhibits high elasticity, hydrolysis resistant, oil resistance and an outstanding low compression set. This product is particularly suitable for oil seals production. The product can be injection molded. Suggested Applications:

Gaskets, Oil Rings, Seals, Packing, Boots, Pads, Hoops, Tubes, Shoes.

| General Information | | | | |
|------------------------------|-------------------------------|-------|-------------|--|
| Features | Low compressive deformability | | | |
| | High elasticity | | | |
| | Hydrolysis resistance | | | |
| | Oil resistance | | | |
| | General | | | |
| | | | | |
| Uses | Packaging | | | |
| | Washer | | | |
| | Pipe fittings | | | |
| | Seals | | | |
| | General | | | |
| | Footwear | | | |
| | | | | |
| Processing Method | Injection molding | | | |
| Physical | Nominal Value | Unit | Test Method | |
| Specific Gravity | 1.20 | g/cm³ | ASTM D792 | |
| Hardness | Nominal Value | Unit | Test Method | |
| Durometer Hardness (Shore A) | 95 | | ASTM D2240 | |
| Elastomers | Nominal Value | Unit | Test Method | |
| Tensile Stress | | | ASTM D412 | |
| 50% strain | 14.0 | MPa | ASTM D412 | |
| 100% strain | 16.0 | MPa | ASTM D412 | |
| 300% strain | 24.0 | MPa | ASTM D412 | |
| Tensile Strength | 33.0 | MPa | ASTM D412 | |
| Tensile Elongation (Break) | 460 | % | ASTM D412 | |
| Tear Strength | 180 | kN/m | ASTM D624 | |
| Compression Set | | | ASTM D395B | |
| 100°C, 22 hr | 30 | % | ASTM D395B | |
| 100°C, 70 hr | 38 | % | ASTM D395B | |
| Injection | Nominal Value | Unit | | |
| Rear Temperature | 210 - 220 | °C | | |

| Middle Temperature | 220 - 230 | °C | |
|--------------------|-----------|----|--|
| Front Temperature | 220 - 230 | °C | |
| Nozzle Temperature | 215 - 225 | °C | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

