

INSPIRE™ 702

Polypropylene

Braskem Europe GmbH

Message:

INSPIRE™ 702 Performance Polymer has been developed for buckets and pails.

Main Characteristics:

Good balance of stiffness and impact properties.

Excellent mould release and long term antistatic performance.

Complies with:

European Commission Regulation (EU) No 10/2011

U.S. FDA FCN 843

Consult the regulations for complete details.

Applications for INSPIRE™ 702 Performance Polymer:

Buckets

Household

Pails

General Information			
Agency Ratings	EU No 10/2011		
	FDA FCN 843		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	45	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus (Injection Molded)	1350	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C, Injection Molded)	6.3	kJ/m ²	ISO 179/1eA

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT