

Paracril® CV

Acrylonitrile Butadiene Rubber

INSA

Message:

Description:

Good green strength.

Readily solvates in mek .

Soluble pvc resin partitioning agent.

Applications:

Adhesives.

Solvent cast seals and grommets.

General Information			
Features	Good Green Strength		
Uses	Adhesives		
	Grommets		
	Seals		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.990	g/cm ³	ASTM D297
Mooney Viscosity (ML 1+4, 100°C)	60 to 75	MU	ASTM D1646
ACN Content - Bound	33.7 to 36.7	wt%	Internal Method
Ash Content	< 0.8	wt%	ASTM D5667
Volatile Matter	< 1.0	wt%	ASTM D5668

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT