

Rilsan® AMN P30 LD

Polyamide 12

Arkema

Message:

Rilsan® AMN P30 LD is a Polyamide 12 (Nylon 12) product. It can be processed by injection molding and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America.

Characteristics include:

- Good UV Resistance
- Heat Resistant
- Mold Release Agent
- Plasticized

General Information				
Additive		Mold Release		
		Plasticizer		
Features		Good UV Resistance		
		High Heat Resistance		
Forms		Pellets		
Processing Method		Injection Molding		
Multi-Point Data		Isothermal Stress vs. Strain (ISO 11403-1)		
		Secant Modulus vs. Strain (ISO 11403-1)		
		Viscosity vs. Shear Rate (ISO 11403-2)		
Physical	Dry	Conditioned	Unit	Test Method
Density	1030	1030	kg/m ³	ISO 1183 ¹
Melt volume-flow rate (235°C/2.16 kg)	61.0	--	cm ³ /10min	ISO 1133 ²
Water Absorption (Saturation)	1.2	--	%	ISO 62 ³
Mechanical	Dry	Conditioned	Unit	Test Method
Tensile modulus	560	545	MPa	ISO 527-2 ⁴
Tensile Stress (Yield)	30.0	28.0	MPa	ISO 527-2 ⁵
Tensile Strain (Yield)	23	22	%	ISO 527-2 ⁶
Nominal strain at break	> 50	> 50	%	ISO 527-2 ⁷
Impact	Dry	Conditioned	Unit	Test Method
Charpy notched impact strength				ISO 179/1eA ⁸
-30°C	3.00	4.00	kJ/m ²	
23°C	11.0	22.0	kJ/m ²	
Charpy impact strength				ISO 179/1eU ⁹
-30°C	No Break	No Break		

23°C	No Break	No Break		
Thermal	Dry	Conditioned	Unit	Test Method
Deflection Temperature Under Load				ISO 75-2 ¹⁰
0.45 MPa	125	--	°C	
1.8 MPa	47.0	--	°C	
Vicat Softening Temperature (50°C/h, B (50N))	133	--	°C	ISO 306 ¹¹
Melting Temperature ¹²	172	--	°C	ISO 11357-3 ¹³
CLTE - Flow	1.4E-4	--	cm/cm/°C	ISO 11359-2 ¹⁴
Electrical	Dry	Conditioned	Unit	Test Method
Surface resistivity	--	5.0E+11	ohms	IEC 60093 ¹⁵
Volume resistivity	--	1.0E+9	ohms·m	IEC 60093 ¹⁶
Electric strength	--	25	kV/mm	IEC 60243-1 ¹⁷
Relative Permittivity				IEC 60250 ¹⁸
100 Hz	13.0	--		
1 MHz	4.00	--		
Dissipation Factor				IEC 60250 ¹⁹
100 Hz	0.38	--		
1 MHz	0.12	--		
Comparative tracking index	--	600		IEC 60112 ²⁰
Flammability	Dry	Conditioned	Unit	Test Method
Burning Behav. at 1.6mm nom. thickn. (1.60 mm)	HB	--		ISO 1210 ²¹
Burning Behav. at thickness h (3.20 mm)	HB	--		ISO 1210 ²²
Oxygen index	20	--	%	ISO 4589-2 ²³
NOTE				
1.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.			
2.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.			
3.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.			
4.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.			
5.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.			
6.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.			

7.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
8.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
9.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
10.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
11.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
12.	10 °C/min
13.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
14.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
15.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
16.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
17.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
18.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
19.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
20.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
21.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
22.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.
23.	Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

