

SIBUR Synthetic Rubber SBR-1712 HI-AR

Grade B

Styrene Butadiene Rubber

SIBUR, LLC

Message:

Oil-extended styrene butadiene synthetic rubber SBR-1712 HI-AR is essentially a styrene (23.5%) and butadiene (76.5%) copolymer obtained by emulsification method with the use of resin/fatty soaps. The copolymer is filled with oil HI-AR.
Product characteristics: Appearance - bale of dark-brown color; weight of a bale - (30 ± 1) kg; packing - a plastic container; shelf life - one (1) year since the date of manufacture

General Information			
Features	Copolymer		
Appearance	Brown		
Forms	Bale		
Physical	Nominal Value	Unit	Test Method
Mooney Viscosity (ML 1+4, 100°C)	46 to 54	MU	ASTM D1646
Bound Styrene	22.5 to 24.5	%	Internal Method
Antioxidant Additive - VS-1	0.30 to 0.70	%	Internal Method
Ash Content	< 0.60	%	ASTM D5667
Oil Content ¹	26 to 29	%	ASTM D5774
Organic Acid	4.0 to 5.6	%	ASTM D5774
Soap - Organic Acid	< 0.30	%	ASTM D5774
Solvent Content - extract	29 to 35	%	Internal Method
Volatile Matter	< 0.60	%	ASTM D5668
Rheometer MDR 2000 ²			ASTM D5289
Maximum Torque (MH) : 160°C	12.0 to 18.5	dNm	
Minimum Torque (ML) : 160°C	1.40 to 3.00	dNm	
Prevulcanization start time (ts1) : 160°C	3.2 to 6.5	min	
Time to 50% vulcanization (T'50) : 160°C	6.5 to 10.5	min	
Time to 90% vulcanization (T'90) : 160°C	12.0 to 18.5	min	
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (300% Strain)	> 9.80	MPa	ASTM D3185
Tensile Strength (Yield)	> 18.0	MPa	ASTM D3185
Tensile Elongation (Break)	> 380	%	ASTM D3185
NOTE			
1.	Oil type: HI-AR		
2.	deformation of 0.5°, MH at 30 min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT