

# Plyophen 43575

Phenolic

Durez Corporation

## Message:

Plyophen 43575 is a liquid one-step phenolic resin.  
Plyophen 43575 is used in coated abrasive manufacture as a general purpose resin. The viscosity can be adjusted with water. It is especially useful in areas having stringent adhesion requirements. It does have excellent wetting ability.

General Information			
Features	Good Adhesion		
Uses	Coating Applications		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.24	g/cm <sup>3</sup>	Internal Method
pH	9.0		Internal Method
Non-Volatile Content	73	%	Internal Method
Sunshine Gel (135°C)	6.1	hr	Internal Method
Water Tolerance	500	%	Internal Method
Thermoset	Nominal Value	Unit	Test Method
Thermoset Mix Viscosity (25°C)	550	cP	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT