

Moplen PP567P

Polypropylene Homopolymer

LyondellBasell Industries

Message:

Moplen PP567P is used in extrusion applications. It has a very narrow molecular weight distribution and it is formulated with an anti-gasfading stabilisation package. Moplen PP567P is used in the production of continuous filaments. Typical applications are high-tenacity yarns (HTY), continuous filaments (CF), bulk continuous filaments (BCF) and spunbond nonwovens. For regulatory information please refer to Moplen PP567P Product Stewardship Bulletin (PSB).

General Information			
Additive	Anti-gas fading		
Features	Gas-fading Resistant		
	Homopolymer		
	Narrow Molecular Weight Distribution		
Uses	BCF Multifilaments		
	Filaments		
	Spunbond Nonwovens		
	Yarn		
Forms	Pellets		
Processing Method	Extrusion		
	Fiber (Spinning) Extrusion		
	Filament Extrusion		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR)	18	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress			ISO 527-2
Yield	33.0	MPa	
Break	21.0	MPa	
Tensile Strain			ISO 527-2
Yield	11	%	
Break	> 500	%	
Flexural Modulus	1300	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength	5.0	kJ/m ²	ISO 179
Charpy Unnotched Impact Strength	150	kJ/m ²	ISO 179
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa, Unannealed)	86.0	°C	ISO 75-2/B

Vicat Softening Temperature			
--	153	°C	ISO 306/A50
--	93.0	°C	ISO 306/B50

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

