# NuSil MED-6010

### Silicone

NuSil Technology

#### Message:

NuSil Technology's restricted materials may be considered for use in short-term implant applications, 29 days or less, or for external applications. Low consistency elastomers (LCEs) are useful alternatives to liquid silicone rubber (LSR) and high consistency rubber (HCR) for end users who need a low viscosity elastomer which provides other unique properties.

LCEs lend themselves to applications that require a pourable, self-leveling silicone. Applications include: encapsulating a device, backfilling a void, potting an electronic component that cannot withstand exposure to high heat, or prototyping a mold. Comments: 1.43 R.I., OPTICALLY CLEAR

General Information				
Features	Good Processability			
	Low Viscosity			
Uses	Electrical/Electronic Applications			
	Medical/Healthcare Applications			
A				
Agency Ratings		USP Class VI		
Appearance	Clear/Transparent			
Processing Method	Encapsulating			
	Potting			
Optical	Nominal Value			
Refractive Index	1.430			
Thermoset	Nominal Value	Unit		
Thermoset Components				
Part A	Mix Ratio by Weight: 1.0			
Part B	Mix Ratio by Weight: 1.0			
Additional Information	Nominal Value	Unit		
Cure System	Platinum			
Uncured Properties	Nominal Value	Unit		
Density	1.05	g/cm <sup>3</sup>		
Viscosity				
<sup>1</sup>	12	Pa·s		
2	18	Pa·s		
Curing Time (150°C)	0.50	hr		
Pot Life (25°C)	210	min		
Cured Properties	Nominal Value	Unit		
Shore Hardness (Shore A)	45			
Tensile Strength	5.52	MPa		
Tensile Elongation at Break	130	%		

Tear Strength	5.25	kN/m
NOTE		
1.	Part B	
2.	Part A	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

