

POLYFLON™ F-301

Polytetrafluoroethylene

DAIKIN AMERICA, INC.

Message:

Daikin-Polyflon PTFE F-301 is a high molecular weight polytetrafluoroethylene fine powder resin for paste extrusion. F-301 has been specifically designed for the manufacture of unsintered tapes, sintered tapes, coated wire and tubing at low to medium reduction ratios.

General Information			
Features	High molecular weight		
Uses	Strap		
	Wire sheath		
	Pipe fittings		
Appearance	White		
Forms	Powder		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	2.15 - 2.18	g/cm ³	ASTM D4895
Apparent Density	> 0.40	g/cm ³	ASTM D4895
Particle Size	400 - 650	μm	ASTM D4895
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	> 25.0	MPa	ASTM D4895
Tensile Elongation (Break)	> 350	%	ASTM D4895
Extrusion instructions			

Extrusion Pressure: 140 to 200 kg/cm²

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

