

Fainplast PVC PMP 001/14

Polyvinyl Chloride + PUR

Fainplast Compounds S.r.l

Message:

Fainplast PVC PMP 001/14 is a Polyvinyl Chloride + PUR (PVC+PUR) product. It can be processed by extrusion or profile extrusion and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America.

General Information

Uses	Profiles
Processing Method	Extrusion Profile Extrusion

Physical	Nominal Value	Unit	Test Method
----------	---------------	------	-------------

Density	1.18	g/cm ³	ISO 1183
---------	------	-------------------	----------

Hardness	Nominal Value	Unit	Test Method
----------	---------------	------	-------------

Shore Hardness (Shore A)	60		ISO 868
--------------------------	----	--	---------

Mechanical	Nominal Value	Unit	Test Method
------------	---------------	------	-------------

Tensile Stress (Break)	> 20.0	MPa	ISO 527-2
------------------------	--------	-----	-----------

Tensile Strain (Break)	> 510	%	ISO 527-2
------------------------	-------	---	-----------

Abrasion Resistance	35.0	mm ³	DIN 53516
---------------------	------	-----------------	-----------

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT