

Borealis PE MA8200

Low Density Polyethylene

Borealis AG

Message:

Borealis PE MA8200 is a Low Density Polyethylene product. It can be processed by injection molding and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Applications of Borealis PE MA8200 include caps/lids/closures and containers.

Characteristics include:

High Gloss

Impact Resistant

General Information			
Features	Good Impact Resistance		
	High Gloss		
	Low Density		
	Low Molecular Weight		
	Narrow Molecular Weight Distribution		
Uses	Caps		
	Pails		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	7.5	g/10 min	ISO 1133

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

