NuSil GEL1-8155

Silicone

NuSil Technology

Message:

As a low stress alternative for electronic packaging, NuSil Technology's silicones allow the designer to choose levels of packaging. We have an extensive line of encapsulants, adhesives, and greases to choose from. These conductive silicones for Thermal Interface Materials (TIM) or for EMI and RFI shielding applications. Benefits of Silicone for Electronics: Wide Operating Temperature Range of -115 °C to 250 °C Low moisture absorption, < 0.4% Typical Corrosion Resistance High Dielectric Strength > 500 V/mil (0.001 inch) or 20 kV/mm Fillers can be added to provide thermal and electrical conductive properties Low Modulus (Typically less than 5.5 MPa/800 psi) Stable chemical and mechanical properties when exposed to high temperatures Low Shrinkage Available as gels, elastomers, film adhesives sheeting, and greases General Purpose: Gels Comments: Firm gel, Penetration 0.4 mm, Longer Work Time	-
General Information	
Features Good Corrosion Resistance	
Good Thermal Stability	
Low Moisture Absorption	
Low Shrinkage	

Uses	Electrical/Electronic Applications	
Forms	Gel	
Thermoset	Nominal Value	Unit
Thermoset Components		
Part A	Mix Ratio by Weight: 1.0	
Part B	Mix Ratio by Weight: 1.0	
Additional Information	Nominal Value	Unit
Cure System	Platinum	
Operating Temperature	-65 to 200	°C
Uncured Properties	Nominal Value	Unit
Color	Translucent	
Viscosity	15	Pa·s
Curing Time (150°C)	0.50	hr

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

