

Jackdaw ABS/PC FR12WT6702

Polycarbonate + ABS

Jackdaw Polymers

Message:

Jackdaw ABS/PC FR12WT6702 is a Polycarbonate + ABS (PC+ABS) product filled with 10% glass fiber. It is available in Europe. Primary characteristic: flame rated.

General Information			
Filler / Reinforcement	Glass Fiber,10% Filler by Weight		
Appearance	White		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.30	g/cm ³	ASTM D792, ISO 1183
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress			
Break	70.0	MPa	ISO 527-2
--	70.0	MPa	ASTM D638
Tensile Elongation (Break)	5.0	%	ASTM D638, ISO 527-2
Flexural Modulus	3500	MPa	ASTM D790, ISO 178
Flexural Strength	50.0	MPa	ASTM D790, ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength	7.0	kJ/m ²	ISO 179
Charpy Notched Impact Strength ¹	7.00	kJ/m ²	ASTM D256
Charpy Unnotched Impact Strength ²	41.0	kJ/m ²	ASTM D256
Charpy Unnotched Impact Strength	41	kJ/m ²	ISO 179
Flammability	Nominal Value		Test Method
Flame Rating	V-0		UL 94
NOTE			
1.	Method B		
2.	Method A		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT