

# NuSil FS-3780

Silicone

NuSil Technology

## Message:

The Aircraft Industry has used silicone adhesives and coatings for over five decades. Silicone's ability to maintain its elasticity and low modulus over a broad temperature range provides excellent utility in extreme environments. Recent advances in material technology provide more opportunities for the Aircraft engineer in choosing the best material for an intended application. Examples of NuSil's capabilities in custom silicones for Aircraft are demonstrated in the following sections.

Fuel Resistance

Static Dissipation and Electrically Conductive Silicones

Ice-Phobic Coatings

General Purpose: High Consistency Rubber

Comment: Extrusion or Compression Molding

General Information	
Features	Electrically Conductive Fuel Resistant
Uses	Aircraft Applications
Processing Method	Compression Molding Extrusion

Additional Information	Nominal Value	Unit
Cure System	Peroxide	
Operating Temperature	-50 to 200	°C
Uncured Properties	Nominal Value	Unit
Color	Translucent	
Density	1.44	g/cm <sup>3</sup>
Curing Time (116°C)	0.083	hr
Cured Properties	Nominal Value	Unit
Shore Hardness (Shore A)	51	
Tensile Strength	9.94	MPa
Tensile Elongation at Break	300	%
Tear Strength	23.6	kN/m

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: [sales@su-jiao.com](mailto:sales@su-jiao.com)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

