

Lifolit® E 60.1451/1 Glow i. t. Dark 6024

Flexible Polyvinyl Chloride

Müller Kunststoffe GmbH

Message:

Processing: Extrusion, technical parts with after glow effect

Stabilizer: Ca/Zn

General Information			
Additive	Calcium-Zinc Stabilizer		
Features	Good Processability		
	Recyclable Material		
Uses	Engineering Parts		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.18	g/cm ³	ISO 1183/A
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A, 3 sec)	57 to 63		DIN 53505
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress	> 9.00	MPa	DIN 53504-S1
Tensile Strain (Break)	> 300	%	DIN 53504-S1
Extrusion	Nominal Value	Unit	
Melt Temperature	130 to 155	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT