

# Caltex PP MT14

Polypropylene

GS Caltex

Message:

Caltex PP MT14 is a Polypropylene material filled with mineral. It is available in Asia Pacific.

Important attributes of Caltex PP MT14 are:

Heat Resistant

High Stiffness

Typical application of Caltex PP MT14: Sheet

General Information			
Filler / Reinforcement	Mineral		
Features	High Heat Resistance		
	High Stiffness		
Uses	Sheet		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.24	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR)	1.7	g/10 min	ASTM D1238
Molding Shrinkage			ASTM D955
Flow	1.0	%	
Across Flow	0.90	%	
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	85		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	24.5	MPa	ASTM D638
Tensile Elongation (Break)	30	%	ASTM D638
Flexural Modulus	2940	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	69	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	132	°C	ASTM D648
Vicat Softening Temperature	150	°C	ASTM D1525
Injection	Nominal Value	Unit	
Processing (Melt) Temp	230 to 250	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

