

ANYPOL SE-250LL

Expanded Polystyrene

SH Energy & Chemical

Message:

ANYPOL EPS Resin is an expandable bead, which contains a blowing agent. According to the applications, it is divided into Self-extinguishable & General Purpose Grade and ANYPOL EPS Resin is an environmentally friendly product which it is possible to satisfy the customer's requirements immediately for special grades since the Production Tehnology of ANYPOL EPS Resin has been developed by our own R&D.

It acquired American UL(UL94HF-1) Standard, Flame Retardant Standard as self -extinguishing, environmentally intimate, future-oriented EPS suitable for insulation plate panel and shock-absorbing packing material that has a blowing agent content below 5% and good expansion ratio & rate.

Properties:

Short aging time

Good molding process

Short cycle time and good fusion

Low thermal conductivity and good strength

General Information	
Additive	Blowing Agent (< 5%)
Features	Expandable
	Good Processability
	Good Strength
	Self Extinguishing
	Thermally Conductive
Uses	Insulation
	Packaging

Physical	Nominal Value	Unit
Density	0.0200 to 0.0300	g/cm ³
Additional Information	Nominal Value	Unit
Bead Size	680.0 to 900.0	μm

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT