Daelim Po1y® 5070(UV)

High Density Polyethylene

DAELIM INDUSTRIAL CO., LTD.

Message:

Daelim Po1y® 5070(UV) is a high density polyethylene product. It can be processed by blow molding and is available in the Asia-Pacific region. Daelim Po1y® 5070(UV) applications include container and food contact applications. Features include: High resistance to environmental stress fracture (ESCR) Good processability accessible food Good UV resistance Impact resistance

General Information			
Features	Ultra-high impact resistance		
	High ESCR (Stress Cracking Resistance)		
	High melt stability		
	Good UV resistance		
	Workability, good		
	Compliance of Food Exposure		
Uses	Industrial container		
Agency Ratings	ASTM D 1248, III, Class A, Cat. 5		
	FDA 21 CFR 177.1520		
Forms	Particle		
Processing Method	Blow molding		
Physical	Nominal Value	Unit	Test Method
Density	0.952	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/21.6			
kg)	6.5	g/10 min	ASTM D1238
Environmental Stress-Cracking Resistance (F50)	> 800	hr	ASTM D1693B
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	26.5	МРа	ASTM D638
Tensile Elongation (Break)	600	%	ASTM D638
Flexural Modulus	1080	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (-20°C)	No Break		ASTM D256
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-76.0	°C	ASTM D746
Additional Information			

Injection	Nominal Value	Unit
Processing (Melt) Temp	190 - 230	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

