

Fixmaster Small Pump Repair

Epoxy; Epoxide

Loctite®

Message:

Fixmaster Small Pump Repair is an epoxy; Epoxy resin products contain ceramic fiber fillers. It is available in North America. The application areas of Fixmaster Small Pump Repair include coating applications and repair materials.

Features include:

Corrosion resistance

Wear-resistant

General Information			
Filler / Reinforcement	Ceramic fiber filler		
Features	Good corrosion resistance		
	Good wear resistance		
Uses	Protective coating		
	Metal repair materials		
Appearance	Grey		
Forms	Particle		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	34.5	MPa	ASTM D638
Compressive Strength	103	MPa	ASTM D695
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	121	°C	ASTM D794
Thermoset	Nominal Value	Unit	
Thermoset Components			
Resin	Mixing ratio by capacity: 4.0		
Hardening method	Mixing ratio by capacity: 1.0		
Pot Life (25°C)	45	min	
Demold Time (25°C)	480	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT