## Hostacom M2 U02 102942

## Polypropylene Homopolymer

LyondellBasell Industries

## Message:

Hostacom M2 U02 102942 is a 20% talc filled PP homopolymer, with high stiffness and dimensional stability. The product is available as a customized color matched, pellet form. This grade is delivered in 102942 color version.

For regulatory compliance information, see Hostacom M2 U02 102942 Product Stewardship Bulletin (PSB) and Safety Data Sheet (SDS).

This grade is not intended for medical, pharmaceutical, food and drinking water applications.

| General Information                         |                                   |           |             |
|---|-----------------------------------|-----------|-------------|
| Filler / Reinforcement                      | Talc filler, 20% filler by weight |           |             |
| Features                                    | Good dimensional stability        |           |             |
|   | Rigidity, high                    |           |             |
|   | Homopolymer                       |           |             |
|   |                                   |           |             |
| Uses  | Application in Automobile Field   |           |             |
| Appearance                                  | Available colors                  |           |             |
| Forms                                       | Particle                          |           |             |
| Processing Method                           | Injection molding                 |           |             |
| Physical                                    | Nominal Value                     | Unit      | Test Method |
| Density (23°C)                              | 1.04                              | g/cm³     | ISO 1183/A  |
| Melt Mass-Flow Rate (MFR) (230°C/2.16       |                                   |           |             |
| kg)   | 11                                | g/10 min  | ISO 1133    |
| Melt Volume-Flow Rate (MVR) (230°C/2.16 kg) | 13.0                              | cm³/10min | ISO 1133    |
| Mechanical                                  | Nominal Value                     | Unit      | Test Method |
| Tensile Modulus (23°C)                      | 2600                              | MPa       | ISO 527-2   |
| Tensile Stress (Yield, 23°C)                | 32.0                              | MPa       | ISO 527-2   |
| Impact                                      | Nominal Value                     | Unit      | Test Method |
| Charpy Notched Impact Strength (23°C)       | 3.5                               | kJ/m²     | ISO 179/1eA |
| Charpy Unnotched Impact Strength (23°C)     | 40                                | kJ/m²     | ISO 179/1eU |
| Thermal                                     | Nominal Value                     | Unit      | Test Method |
| Heat Deflection Temperature                 |                                   |           |             |
| 0.45 MPa, not annealed                      | 120                               | °C        | ISO 75-2/B  |
| 1.8 MPa, not annealed                       | 70.0                              | °C        | ISO 75-2/A  |
| Vicat Softening Temperature                 | 95.0                              | °C        | ISO 306/B   |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

