

ARNYL 6 30% FV NATURALE

Polyamide 6

Daloga srl

Message:

ARNYL 6 30% FV NATURALE is a Polyamide 6 (Nylon 6) material. It is available in Europe.

General Information			
Appearance	Natural Color		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.35	g/cm ³	ASTM D792
Ash Content - 1 hrs (750°C)	30	%	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	115	MPa	ASTM D638
Tensile Elongation (Break)	4.9	%	ASTM D638
Flexural Modulus	8000	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	95	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load			ASTM D648
0.45 MPa, Unannealed	220	°C	
1.8 MPa, Unannealed	210	°C	
Vicat Softening Temperature			
--	220	°C	ASTM D1525 ¹
--	215	°C	ASTM D1525 ²
Melting Temperature	222	°C	DSC
NOTE			
1.	Loading 1 (10 N)		
2.	Loading 2 (50 N)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT