

Sinvicomp SFE6500

Flexible Polyvinyl Chloride

Teknor Apex Asia Pacific PTE. LTD.

Message:

Sinvicomp SFE6500 is a Flexible Polyvinyl Chloride material. It is available in Asia Pacific for extrusion.

Important attributes of Sinvicomp SFE6500 are:

Food Contact Acceptable

Non-Toxic

Typical application of Sinvicomp SFE6500: Hose/Tubing

General Information			
Features	Food Contact Acceptable		
	Non-Toxic		
Uses	Hose		
	Tubing		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.21	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	68		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	14.7	MPa	ASTM D638
Tensile Elongation ² (Break)	320	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Thermal Stability ³ (190°C)	> 50	min	BS 2782
NOTE			
1.	250 mm/min		
2.	250 mm/min		
3.	Congo Red		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

