

HANWHA P-800

Polyvinyl Chloride

Hanwha Chemical

Message:

Feature: Excellent thermal resistance and easy processing /good for injection mold products due to high liquidity

Use: Hard sheets, foaming pipe, hard plate, fitting, injection mould and non-toxic sheet

General Information			
Features	Good Processability		
	Good Thermal Stability		
Uses	Fittings		
	Foam		
	Piping		
	Sheet		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.51 to 0.59	g/cm ³	ASTM D1895
Particle Size - 42Mesh(350µm) Sieve Pass %	100	%	Internal Method
Volatile Matter	< 0.30	%	ASTM D3030
Degree of Polymerization			
DP	750 to 850		JIS K6720-2
K-Value	61.0		DIN 53726

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT