# **LOXIM 811 02T HB**

## Polypropylene Copolymer

### **LOXIM Industries Private Limited**

#### Message:

LOXIM 811 02T HB is a Polypropylene Copolymer (PP Copolymer) product filled with 10% talc. It is available in Asia Pacific.

Characteristics include:

Flame Rated

Copolymer

General Information				
Filler / Reinforcement	Talc,10% Filler by Weight	Talc,10% Filler by Weight		
Features	Copolymer			
Appearance	Colors Available			
	Opaque			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	0.918 to 1.02	g/cm³	ASTM D792	
Molding Shrinkage - Flow	1.5 to 1.7	%	ASTM D1299	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	28.0 to 30.0	MPa	ASTM D638	
Flexural Modulus	1600 to 1700	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact	80 to 100	J/m	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load (0 MPa, Unannealed)	.45 98.0 to 102	°C	ASTM D648B	
Flammability	Nominal Value		Test Method	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

UL 94

#### Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

ΗВ

Tel: +86 21 5895 8519

Phone: +86 13424755533

Flame Rating (1.60 mm)

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

