

# DIGITALWAX® DL 260

Unspecified  
DWS Systems

## Message:

Photosensitive Resin for DigitalWax® X Series Stereolithography Systems

DL 260 Moulding Resin is a nano-filled ceramic resin specially developed for rubber moulding applications, including VLT, liquid silicones and vulcanized rubber at medium-low temperatures (max. 90°C).

DL260 Moulding Resin is suitable both for thin and thick models. DL260 Moulding Resin can be used to make rubber moulds with liquid silicones and rubber vulcanized at a maximum temperature of 90°C. Models made of DL260 resin can be removed easily from the rubber mould and they can also be broken, allowing you to carry out some difficult cuts that would be even impossible with a metal model. DL260 delivers extremely smooth surfaces and exceptionally precise and sharp details.

Features

- Smooth surface
- High resolution
- High accuracy
- No further manual finishing needed

General Information		
Filler / Reinforcement	Unspecified Nano	
Features	Filled	
	Good Mold Release	
	Good Surface Finish	
Uses	Modeling Material	
	Mold Making	
	Thick-walled Parts	
	Thin-walled Parts	
Appearance	Blue	
	Opaque	
Forms	Liquid	
Processing Method	3D Printing, Stereolithography	
Physical	Nominal Value	Unit
Viscosity <sup>1</sup> (25°C)	1.50 to 2.20	Pa · s
Hardness	Nominal Value	Unit
Durometer Hardness (Shore D)	88	
Mechanical	Nominal Value	Unit
Flexural Modulus	1820	MPa
Flexural Strength	73.1	MPa
NOTE		
1.	Liquid Resin	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any

infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

