

Sinpolene MBB0031

Linear Low Density Polyethylene

Teknor Apex Asia Pacific PTE. LTD.

Message:

Sinpolene MBB0031 is a polyethylene-based black masterbatch designed specifically for use in generally-purpose film, blow moulding, injection moulding and extrusion of polyolefins. Sinpolene MBB0031, has high pigment loading and thus offers high colouring value with good quality and performance. MBB0031 contains extender, which give anti-blocking properties.

CHARACTERISTICS

-
- Easy processing
-
- Minimal wear effect on processing equipment

General Information			
Features	General		
Uses	Films		
RoHS Compliance	RoHS compliance		
Forms	Particle		
Processing Method	Blow film		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.49	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/10.0 kg)	3.0 - 25	g/10 min	ASTM D1238
Moisture Content		%	ASTM D3030
Carbon Black Content	25	%	ASTM D1603
Additional Information			

Recommended dosage: 2 - 5%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

