

Sinpolene MBN7541

Linear Low Density Polyethylene
Teknor Apex Asia Pacific PTE. LTD.

Message:

SINPOLENE MBN7541 contains plastic processing aids to eliminate and reduce melt fracture and mold deposits generated during linear and high density polyethylene processing, effectively increase extrusion and reduce power consumption.

General Information	
Additive	Processing aids (3%)
Features	The smell is low to none
Uses	Sheet
	Profile
Forms	Particle
Processing Method	Sheet extrusion molding
	Profile extrusion molding
	Injection molding

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) ¹ (190°C/2.16 kg)	3.0 - 6.0	g/10 min	ASTM D1238

Additional Information

推荐用量: 2.0-4.0%

NOTE


1. degree C, PE Base

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT