

BB-AMIDE 5033

Polyamide
BB Resins S.r.l.

Message:

BB-AMIDE 5033 is a medium low viscosity reactive polyamide resin.
This resin is designed for use with solid or liquid epoxy resins to give tough, chemical resistant thermoset coatings with room temperature cure.
BB-AMIDE 3033/epoxy resin systems are used in maintenance coatings, and high solids enamel paint formulations.

General Information		
Features	Good Chemical Resistance	
	Good Toughness	
	Medium Reactivity	
	Medium-low Viscosity	
Uses	Coating Applications	
	Paint	
Appearance	Amber	
Forms	Liquid	
Physical	Nominal Value	
Gardner Color	< 10.0	
Brookfield Viscosity (25°C)	6.00 to 8.00	Pa · s
Active Content	100	%
Amine Value	370 to 420	mg KOH/g
Mixing Ratio		
with liquid epoxy resin	50	%
with solid epoxy resin	30	%
Thermoset	Nominal Value	Unit
Pot Life		
25°C ¹	120	min
25°C ²	1400 to 2900	min
NOTE		
1.	on 200 g mass with liquid epoxy resin	
2.	on 200 g mass with solid epoxy resin	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

