

PETILEN F2-26TO

Low Density Polyethylene

PETKIM Petrokimya Holding A.S.

Message:

PETILEN F2-26TO is a low density polyethylene product. It can be processed by film extrusion and is available in North America, Europe or Asia Pacific. The application fields of PETILEN F2-26TO include packaging and movies.

General Information			
Uses	Packaging		
	Films		
Forms	Particle		
Processing Method	Film extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.924 - 0.928	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.1 - 3.0	g/10 min	ASTM D1238
Ash Content	0.1	wt%	
Optical	Nominal Value	Unit	Test Method
Gloss	78		ASTM D2457
Haze	6.3	%	ASTM D1003

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

