

Vinnolit® E 2169

Semi-Rigid Polyvinyl Chloride

Vinnolit GmbH & Co. KG

Message:

Vinnolit E 2169 is an emulsion polymer primarily used to make semi-rigid and flexible profiles and film as well as flooring.

General Information			
Uses	Film		
	Flooring		
	Profiles		
Agency Ratings		EC 1907/2006 (REACH)	
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.50	g/cm ³	ISO 60
K-Value	69.0		ISO 1628-2
Viscosity Number (Reduced Viscosity)	120.0	ml/g	ISO 1628
Particle Size Distribution ¹	< 0.10	%	ISO 4610
Volatile Matter	< 0.50	%	ISO 1269
NOTE			
1.	retained on 0.250 mm screen		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT