NEMCON H ABS DP116P

Acrylonitrile Butadiene Styrene

Ovation Polymers Inc.

Message:

Nemcon H-series products are designed for use in high performance electronic assemblies where heat removal is critical to system performance. Nemcon H ABS DP116P is a thermally conductive, electrically insulating ABS compound, combining thermal conductivity with good HDT and processability.

General Information			
Features	Heat conduction		
	Insulation		
	Workability, good		
	Heat resistance, high		
Uses	Electrical/Electronic Applications		
	Electrical components		
	Electrical housing		
	Shell		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.66	g/cm³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus ¹ (23°C)	3570	MPa	ASTM D638
Tensile Strength ² (Break, 23°C)	32.0	MPa	ASTM D638
Tensile Elongation ³ (Break, 23°C)	1.7	%	ASTM D638
Flexural Modulus ⁴ (23°C, 50.0 mm Span)	3190	MPa	ASTM D790
Flexural Strength ⁵ (Break, 23°C, 50.0 mm			
Span)	52.0	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	21	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed, 3.20 mm)	81.0	°C	ASTM D648
Thermal Conductivity (23°C)	0.70	W/m/K	ASTM C177
·	Nominal Value		
Electrical Surface Posistivity	8.0E+12	Unit	Test Method ASTM D257
Surface Resistivity Additional Information	0.00+12	UIIIIS	ASTIVI DZ31
The value listed as Thermal Conductivity, AS	TM C177 was tosted in asserdance	+b ACTM E1461	
•	orivi C177 was lested in accordance wi	UI ASTIVI E1401.	
NOTE 1	E0 mm/mir		
1.	50 mm/min		
2.	50 mm/min		

3.	50 mm/min
4.	1.3 mm/min
5.	1.3 mm/min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

