SQUARE® SSR2018-40

Silicone

Shenzhen SQUARE Silicone Co., Ltd.

Message:

Silicone rubber for medical pipe catalyzed by peroxidet in extruding mould:

Product Description

SQUARE® SSR2018-XX is high transparence and high tear strength solid silicone rubber, suitable for extrusion or compression molding processes.

Key Features

High transparence

High tensile strength and high tear strength

Good rebound property

Excellent thermal and cold stability(-60° to 250°C)

Low yellowing

Outstanding resistance to ageing

Comply with US FDA CFR 21.Part.177.2600 and EN1616 and RoHS standard and Meet ISO 10993 biological reactivity test,

Application

SQUARE® SSR2018-XX is suitable for making medical pipe etc.

General Information					
Features	High tensile strength				
reatures	Good tear strength				
	Definition, high				
	Thermal stability, good				
	mermai stability, good				
Uses	Piping system				
	Medical/nursing supplies				
Agong, Patings	EDA 21 CED 177 2600				
Agency Ratings	FDA 21 CFR 177.2600				
	ISO 10993				
RoHS Compliance	RoHS compliance				
Appearance	Clear/transparent				
Processing Method	Extrusion				
	Compression molding				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.08	g/cm³	ASTM D792		
Molding Shrinkage - Flow	3.0	%	JIS K6301		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A)	40		ASTM D2240		
Elastomers	Nominal Value	Unit	Test Method		
Tensile Strength	7.00	MPa	ASTM D412		
Tensile Elongation (Break)	600	%	ASTM D412		
Tear Strength ¹	35.0	kN/m	ASTM D624		

Compression Set (175°C, 22 hr)	22	%	DIN 53517
Thermoset	Nominal Value	Unit	
Shelf Life	100	wk	
Uncured Properties	Nominal Value	Unit	
Curing Time (170°C)	0.17	hr	
NOTE			
1.	B mould		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

