

PURGOVIN® 3000

Polyvinyl Chloride

Axiall Corporation

Message:

PURGOVIN®3000 is a unique vinyl based purging compound designed for use in the shutdown or cleaning of extrusion lines. The use of PURGOVIN®3000 in the purging process of polymers other than vinyl compounds may result in rapid chemical decomposition, causing equipment damage or pressure buildup. This is known to occur with Acetals and Polycarbonates.

PURGOVIN®3000 offers excellent heat stability and can be used to:

Terminate a production run in preparation for complete machine disassembly and cleaning

Shutdown a machine for an extended period without disassembly

Purge a machine without shutting down during product, die, or other process changes

Purge a machine during production on a problem prevention basis

PURGOVIN®3000 is available in 1,000 pound multi-wall boxes in powder blend form.

General Information			
Features	Sprayable		
Uses	Cleaning compound		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.58 - 1.62	g/cm ³	ASTM D792

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT