

Sylvin 7403-90 Natural

Polyvinyl Chloride

Sylvin Technologies Incorporated

Message:

Sylvin 7403-90 Natural Is An Alloy Compound Formulated For Electrical Molding Applications That Require Bondability To Other Materials.

General Information			
Features	Bondability		
Uses	Electrical Parts		
Appearance	Natural Color		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.28	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	90		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	8.27	MPa	ASTM D638
Tensile Elongation (Break)	300	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	39.4	kN/m	ASTM D624
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	171 to 182	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

