

Lusin® Lub PZO 152

Unspecified

Chem-Trend L.P.

Message:

Special Lubricating and Assembly Paste

Benefits

Resistant to high pressure

Prevents stick slip

Protects against corrosion

Prevents fretting corrosion

Resistant to hot water and steam

Resistant to alkaline and acid media

Spreads easily

Description

Lusin® Lub PZO 152 is a soft special lubricating and assembly paste based on mineral oil and a combination of inorganic solid lubricants. The multi-purpose paste is resistant to high pressure and protects against corrosion including fretting corrosion.

Lusin® Lub PZO 152 achieves a maximum lubricating effect in the preferred application range up to 150°C (302°F).

Lusin® Lub PZO 152 prevents stick slip, and is resistant to hot water, steam, alkaline and acid media. In addition, it spreads easily and shows a long-lasting performance.

Typical Properties

Appearance of the active ingredient : Beige, paste

Application

Lusin® Lub PZO 152 is recommended for the use on core slides and ejector pins in plastics processing machines. The lubricant is designed for maintenance and repair purposes, especially for sliding surfaces (low to medium sliding speeds), for applications where there might be stick slip, and for applications under high static and dynamic loads. The product can be used for applications exposed to heat and as assembly aid for all kinds of applications. Lusin® Lub PZO 152 is a multi-purpose product for assembly operations in the entire machine building industry.

General Information			
Features	alkali resistance		
	acid resistance		
	Steam resistance		
Appearance	Beige		
Forms	Adhesive		
Physical	Nominal Value	Unit	Test Method
Density (20°C)	1.350	g/cm ³	DIN 51757
Service Temperature	-30 - 150	°C	
Drop Melt Point	> 150	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

