

Sekisui PVC TG-H500

Polyvinyl Chloride
Sekisui (Hong Kong) Limited

Message:
Sekisui PVC TG-H500 is a polyvinyl chloride product. It is available in the Asia-Pacific region.

General Information			
Appearance	White		
Forms	Powder		
Physical	Nominal Value	Unit	Test Method
Density	1.36	g/cm ³	JIS K7112
Apparent Density	0.50 - 0.60	g/cm ³	JIS K6720-2
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	80		JIS K7215
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	45.0	MPa	JIS K7113
Tensile Strain (Break)	130	%	JIS K7113
Flexural Stress	69.0	MPa	JIS K7171
Impact	Nominal Value	Unit	Test Method
Charpy Unnotched Impact Strength			JIS K7111
0°C	7.0	kJ/m ²	JIS K7111
20°C	11	kJ/m ²	JIS K7111
Thermal	Nominal Value	Unit	Test Method
Heat Loss		wt%	JIS K6720-2
Grain Size ¹	100	%	Internal method
Temperature - Flex	66	°C	JIS K6745
degree of polymerization-Mean	500		JIS K6720-2
Thermal Decomposition Temperature	68	°C	JIS K7191-1
Additional Information	Nominal Value	Unit	Test Method
Flow Rate: 200 ml/sec			
NOTE			

1.

The percentage that passes JIS Sieve#40

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

